
VANTA Specifications



Vanta™ Handheld XRF Analyzer

Rugged. Revolutionary. Productive.

Vanta™ handheld XRF analyzers are rugged and built for analytically demanding applications in the harshest environments. Vanta analyzers are IP rated for protection against dust and water, are drop tested, and built to withstand extreme ambient temperatures.

Vanta analyzers provide fast, accurate elemental analysis. Each device features Olympus' Axon Technology™, a revolution in XRF signal processing that provides accurate, repeatable results for greater productivity and a fast return on investment. Vanta analyzers feature an intuitive interface so new users can work with the device with minimal training. Data is easily exported wirelessly or via USB.

The Vanta™ Series

No matter the model, each Vanta™ analyzer is engineered for durability and analytical superiority. Olympus manufactures Vanta analyzers to suit a variety of applications, depending on your needs.

M Series

Our fastest, most powerful Vanta analyzers feature exceptional performance.

C Series

The C series combine value with superior speed, limits of detection (LODs), and elemental range.

L Series

The L series is an economical yet full-featured PIN detector analyzer.

Element

The Vanta Element provides ease of use and efficient data management in an entry level package with streamlined capabilities.

Vanta Specifications

Dimensions (W × H × D)	8.3 cm × 28.9 cm × 24.2 cm (3.25 in. × 11.4 in. × 9.5 in.)
Weight	M series, C series, and L series: 1.70 kg (3.75 lb) with battery, 1.48 kg (3.24 lb) without battery Element: 1.54 kg (3.39 lb) with battery, 1.32 kg (2.91 lb) without battery
Excitation Source	4-watt X-ray tube with application-optimized anode material (rhodium (Rh), silver (Ag), or tungsten (W)) M series (Rh & W) and C series (Ag): 8–50 kV C series (Rh & W): 8–40 kV L series (W) and Element (W): 35 kV (2 watts)
Primary Beam Filtration	M and C series: 8-position autoselected filter per beam per mode; optional collimation to 3 mm diameter beam spot L series and Element: Fixed aluminum filter and no internal collimation
Detector	M series: Large-area silicon drift detector C series: Silicon drift detector L series and Element: Silicon PIN detector
Power	Removable 14.4 V Li-ion battery with hot-swap capability (M, C, and L series only) or 18 V power transformer 100–240 VAC, 50–60 Hz, 70 W max
Display	800 × 480 (WVGA) LCD with capacitive touch screen supporting gesture control
Operating Environment	Temperature range for the M, C, and L series: –10 °C to 50 °C (14 °F to 122 °F), (continuous duty cycle with optional fan); Temperature range for the Element: –10 °C to 45 °C (14 °F to 113 °F) Humidity: 10% to 90% relative humidity non-condensing
Drop Test	Military Standard 810-G 4-foot (1.3 M) drop test
IP Rating and Detector Shutter	M series, and Element IP54: dust protected and protected against water splashing from all directions C and L series IP55: dust protected and protected against water jets from all directions M and C series: Solid detector shutter to help prevent detector damage
Pressure Correction	M and C series: Built-in barometer for automatic altitude and air density correction
GPS	M, C, and L series: Embedded GPS / GLONASS receiver
Operating System	Linux® Cloud enabled with user fleet manager capability
Data Storage	microSD™ slot with removable 1 GB industrial SD card included
USB	(2) USB 2.0 type A host ports for accessories such as wireless LAN, Bluetooth®, and USB flash drives. (1) USB 2.0 type mini-B port for connection to computer.
Wireless LAN	Supports 802.11 b/g/n (2.4 GHz) cable optional USB adaptor
Bluetooth	Supports Bluetooth® with an optional USB adaptor
Aiming Camera	Full VGA CMOS camera (Optional on M, C, and L series)
Panoramic Camera	5-megapixel CMOS camera with autofocus lens (Optional on M, C, and L series)
Warranty	M, C, and L series: Three-year warranty; Element: One-year warranty
Selected Optional Accessories	M, C, and L series: Field Stand, Soil Foot, Holster, Work Station, Weld Mask, Hot Heel, Probe Shield, and VLW Collimation Mask (L series only) Element: Field Stand, Soil Foot, and Holster



Via Guido Rossa 14
23875 Osnago (LC) - Italy
Tel. +39 039 9280061
Fax. +39 039 9289636
info@quantanalitica.com
www.quantanalitica.com

OLYMPUS SCIENTIFIC SOLUTIONS AMERICAS
is certified to ISO 9001, ISO 14001, and OHSAS 18001.

All specifications are subject to change without notice.
All brands are trademarks or registered trademarks of their respective owners and third-party entities.
The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Olympus Corporation is under license. microSD is a trademark of SD-3C, LLC. Linux is a registered trademark of Linus Torvalds in the U.S. and other countries. Olympus is a registered trademark, and Vanta and Axon Technology are trademarks of Olympus Corporation. Copyright © 2019 by Olympus.

www.olympus-ims.com

OLYMPUS®

OLYMPUS CORPORATION OF THE AMERICAS
48 Woerd Avenue, Waltham, MA 02453, USA, Tel.: (1) 781-419-3900
110 Magellan Circle, Webster TX, 77598, USA, Tel.: (1) 281-922-9300

For inquiries - contact
www.olympus-ims.com/contact-us



EM440035EN